Custom Fabricating & Supplies

Specification Sheet

Product Name
F032RB – Double Sided Polyethylene Foam Tape

Description
F032RB is a Double Coated Foam Tape, it's solvent-based rubber pressure sensitive adhesive tape that offers very high shear strength and good initial tack. Ideal for various mounting, joining and sealing applications.

Applications
Excellent for bonding heavy-duty hanger hooks in indoor environments, joining and mounting of nameplates, plastics, bonding of Point of Purchase displays and graphics, and for fixing of plastic or metal items.

Technical Properties

Adhesive System	Solvent Rubber
Carrier	Polyethylene Foam
Foam Density	6 PCF
Liner Thickness	3 Mil
Liner Density	#60 (90 g/m^2)
Liner Material	Glassine Paper
Liner Color	White
Tape Thickness	1/32" (0.8 ± 0.2 mm)
Tack	J. Dow No. 7
Peel Adhesion	PSTC-3 123 oz/inch (over 3.5 kg/25mm)
Shear Strength	Over 100hrs w/ 70.6 oz loading 1"X1" (2.0 KG/25mmX25mm) bonding 2
PSTC-9	stainless steel plates at 77° F (25° C)
Service Temperature	14° F ~ 122° F (-10° C ~ 50° C)
Tape Color	White

The information on this data sheet is based on laboratory test data we believe to be accurate, relevant and reliable. Please look upon these values as guides rather than absolutes. Since actual service conditions for a given application may vary substantially from standard laboratory conditions, specific recommendations or warranties relative to a specific end use cannot be made. The buyer is urged to conduct its own investigations and qualification tests to determine suitability for its intended application. CFS shall not be liable for any damages arising out of the use of any of its guide specifications.