



Custom Fabricating & Supplies

5500 West Oakwood Park Drive • Franklin, WI 53132

Phone: 800.556.7188 • 414.421.2600

Fax: 414.421.2700

info@customfabricate.com

www.customfabricate.com

PRODUCT	USAGE	MAX. TEMP.	LENGTH	EQUAL TO
RED PLATING FILM 2 Mil RPT is an industry standard.	Plating Anodizing	425 F	72 yards	3M 1280
YELLOW VINYL TAPE 6 Mil PVC6 is the plating industry standard for w/rubber adhesive.	Plating	180 F	36 yards	3M 764
HIGH TEMP. VINYL TAPE HTGV is an industry stand for electroplating.	Electroplating	220 F	60 yards	Sequoia 4-HTP
ALUMINUM FOIL TAPE AFT is 5 Mil Aluminum foil with acrylic adhesive which is ideal for plating and chemical stripping.	Plating Chemical Stripping	300 F	60 yards	3M 425
3M1280—RED PLATERS POLY 4.2 Mil (0.11 mm) polyester film tape with silicone/rubber blend adhesive. Used for masking during electroplating.	Electroplating		72 yards	CFS-RPT
3M471—ELECTRO PLATING VINYL 5.2 Mil vinyl backing with a rubber adhesive. Conformable w/stretch properties to provide straighter lines, clean removal & good solvent resistance. Multiple colors.	Electroplating	170 F	36 yards	CFS-PVC6
3M421—LEAD FOIL TAPE 6.3 Mil lead foil backing unlined tape used in electroplating & as a moisture & radiation barrier in certain applications. Lead foil backing provides good conformability having electrically and thermally conductive properties.	Electroplating	225 F	36 yards	CFS-LFT
NON-ADHESIVE VINYL NAV is an industry standard for plating & anodizing. Dry vinyl wrap.	Plating Anodizing	175 F	250 or 500 ft.	Sequoia GSV-1
YELLOW VINYL TAPE PVC7, 7 mil vinyl w/rubber adhesive is the plating industry standard.	Plating	210 F	66 feet	Sequoia SC-1
HIGH TEMP. BLUE VINYL Ultra high temp. vinyl tape; highly resistant to chemicals.		300F	300 feet	
LEAD FOIL TAPE 5 Mil lead tape w/rubber adhesive. Great in electroless, nickel & chrome.		180 F		3M420 & 421
3M470 ELECTRO PLATING VINYL 7.1 Mil (0.18 mm), vinyl backing w/rubber adhesive. Excellent resistance to most chemicals used in typical electroplating.	Electroplating	170 F	36 yards	CFS-PVC7
3M420 LEAD FOIL TAPE 6.3 Mil lead foil backing lined tape used in electroplating. Lead foil backing provides good conformability having electrically & thermally conductive properties.	Electroplating	225 F	36 yards	CFS-LFT
3M425 ALUMINUM FOIL TAPE 4.6 Mil, 2 Mil dead-soft aluminum foil w/pressure sensitive acrylic adhesive. Excellent heat & light reflection to protect against high temps. Also serves as great barrier against certain chemicals used in aircraft paint stripping masking.	Plating	300 F	60 yards	CFS-AFT

PRODUCT	USAGE	MAX. TEMP.	LENGTH	EQUAL TO
3M764 General purpose vinyl tape, 5.0 Mil (0.125 mm), vinyl backing w/ rubber adhesive. Great conformability and instant adhesion.	General	80 F	36 yards	
3M250 ADHESIVE TESTING TAPE Scotch flatback masking tape used for applications where a stronger paper backing is needed. Also used to conduct coating adhesion testing according to ASTM D-335.				

OTHER PRODUCTS & SERVICES

Custom Molding



Custom Die Cutting



Custom Fabricating & Supplies
 5500 West Oakwood Park Drive • Franklin, WI 53132
 Phone: 800.556.7188 • 414.421.2600
 Fax: 414.421.2700
info@customfabricate.com
www.customfabricate.com

To contact a Sales Representative in your area, call us at 800-556-7188 or visit our website for details.