

# 9.0mil LOW DENSITY POLYETHYLENE FILM TAPE

## Specification Sheet

### Description:

WPT is a 9.0 mil Low Density Polyethylene Film Tape coated on one side with a Synthetic Rubber Adhesive.

### FEATURES/BENEFITS:

Its adhesive system remains permanently tacky and bonds well to most surfaces over a wide range of temperatures; with excellent low temperature bond. Its tough polyethylene backing offers good abrasion and tear resistance. It is highly conformable, waterproof and resistant to chemical deterioration.

### APPLICATIONS:

Ideal for polyethylene splicing or seaming in construction applications such as stucco fabrication; patching / repairing poly sheeting used in boating and RV industry; surface protection & electroplate masking; wire identification; packaging; etc. Works well in most applications where a low thread count polyethylene coated cloth tape is being used.

### PHYSICAL PROPERTIES:

Total Thickness	9.0 mil (0.229mm)
Adhesive	Rubber
Adhesion to Steel	56 oz/inch
Peel Adhesion	70 oz/inch
Adhesion to Backing	35 oz/inch
Tensile Strength	22 lb/inch width
Elongation	100%

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the products for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.



### **Custom Fabricating & Supplies**

5500 Oakwood Park Drive ~ Franklin, WI 53132

P: 414.421.2600 ~ Toll: 800.556.7188 ~ F: 414.421.2700

[www.customfabricate.com](http://www.customfabricate.com)

