

# ICT — INDUSTRIAL GRADE CREPE TAPE



## Specification Sheet

### Description

A general grade, coarse crepe paper masking tape coated with a pressure sensitive natural rubber based adhesive. Designed primarily as an all-purpose product for non-critical applications.

### Applications

Interior paint masking, mail rooms, school bids, and for light duty bundling, packaging, splicing, and tabbing.

### Technical Properties

- Backing: Course Crepe Paper
- Color: Beige
- Adhesive: Natural/Synthetic Blend
- Adhesion to Steel: 37 (10 N/25mm)  
(oz/in of width)
- Tensile Strength: 15 (65.7 N/25mm)  
(lbs/in of width)
- Elongation: 8  
(% at break) PSTC-31
- Total Thickness: 5.3 (0.13 mm)  
(mils) PSTC-33
- Quick Stick to Steel: 5.5 (1.5 N/25mm)  
(oz/in of width) PSTC-5
- Quick Stick to Kraft: 12 (3.3 N/25mm)  
(oz/in of width) PSTC-5
- Operating Temperature Range: +40°F ~ +225°F  
+4.4°C ~ +71°C

### Shelf Life

Good for 6 months if kept in a 68 degree environment.



### **Custom Fabricating & Supplies**

5500 Oakwood Park Drive ~ Franklin, WI 53132

P: 414.421.2600 ~ T/F: 800.556.7188 ~ F: 414.421.2700

[www.customfabricate.com](http://www.customfabricate.com)

