

Double Sided PVC Tape—D4085

Specification Sheet

Description

Acrylic adhesive coated on both sides, un-plasticized PVC film, mustard color 60# (90g/m²) glassine release paper liner. High peel adhesion and high grab tack, secure bonding. Good resistance to solvent, chemical, UV and heat. Excellent performance of anti-plasticizer migration.

Applications

Permanent bonding result to most substrates, such as Wood, Glass, Cement & Plastic. Fixing to the decorative trim, such as PVC profile for furniture industry. Ideal for mounting nameplates, trophy, luggage tags and labels.

Technical Properties

- Thickness 8.5 MIL (0.21 +/-0.01mm)
- Loop Tack 123 oz/inch (3.5 kg/25mm)
- Peel Adhesion PSTC-3 84 oz./inch 1 kg/25mm
- Shear Strength PSTC-7 Over 24 hours with 1 kg loading on 25 mm x 25 mm at 80° C
- Heat Resistance Over 24 hours with 0.5 kg loading on 25 mm x 25 mm at 80° C
- Application Temp -4° F ~ 194° F (-20° C ~ 120° C)
- Service Temp -22° C ~ 212° F (-30° C ~ 120° C)



Custom Fabricating & Supplies

5500 Oakwood Park Drive ~ Franklin, WI 53132

P: 414.421.2600 ~ T/F: 800.556.7188 ~ F: 414.421.2700

www.customfabricate.com

