

F032R—DOUBLE SIDED POLYETHYLENE FOAM TAPE

Specification Sheet

Description

F032R is a Double Coated Foam Tape, it's solvent-based rubber pressure sensitive adhesive tape that offers very high shear strength and good initial tack. Ideal for various mounting, joining and sealing applications.

Applications

Excellent for bonding heavy-duty hanger hooks in indoor environments, joining and mounting of nameplates, plastics, bonding of Point of Purchase displays and graphics, and for fixing of plastic or metal items.

Technical Properties

• Adhesive System	Solvent Rubber
• Carrier	Polyethylene Foam
• Foam Density	6 PCF
• Liner Thickness	3 MIL
• Liner Density	#60 (90 g/m ²)
• Liner Material	Glassine Paper
• Liner Color	White
• Tape Thickness	1/32" (0.8 ± 0.1 mm)
• Tack	J. Dow No. 7
• Peel Adhesion	PSTC-3 123 oz/inch (over 3.5 kg/25mm)
• Shear Strength PSTC-9	Over 100 hrs with 70.6 oz loading on 1"X1" (2.0 KG/25mmX25mm) bonding 2 stainless steel plates at 77°F (25°C)
• Service Temperature	14°F ~ 122°F (-10° ~ 50°C)
• Tape Color	White



Custom Fabricating & Supplies

5500 Oakwood Park Drive ~ Franklin, WI 53132

P: 414.421.2600 ~ T/F: 800.556.7188 ~ F: 414.421.2700

www.customfabricate.com

