

# F032RB—DOUBLE SIDED POLYETHYLENE FOAM TAPE

## Specification Sheet

### Description

F032RB is a Double Coated Foam Tape, it's solvent-based rubber pressure sensitive adhesive tape that offers very high shear strength and good initial tack. Ideal for various mounting, joining and sealing applications.

### Applications

Excellent for bonding heavy-duty hanger hooks in indoor environments, joining and mounting of nameplates, plastics, bonding of Point of Purchase displays and graphics, and for fixing of plastic or metal items.

### Technical Properties

- Adhesive System Solvent Rubber
- Carrier Polyethylene Foam
- Foam Density 6 PCF
- Liner Thickness 3 MIL
- Liner Density #60 (90 g/m<sup>2</sup>)
- Liner Material Glassine Paper
- Liner Color White
- Tape Thickness 1/32" (0.8 ± 0.2 mm)
- Tack J. Dow No. 7
- Peel Adhesion PSTC-3 123 oz/inch (over 3.5 kg/25mm)
- Shear Strength PSTC-9 Over 100 hrs with 70.6 oz loading on 1"X1" (2.0 KG/25mmX25mm) bonding 2 stainless steel plates at 77°F (25°C)
- Service Temperature 14°F ~ 122°F (-10°C ~ 60°C)
- Tape Color Black



### **Custom Fabricating & Supplies**

5500 Oakwood Park Drive ~ Franklin, WI 53132

P: 414.421.2600 ~ T/F: 800.556.7188 ~ F: 414.421.2700

[www.customfabricate.com](http://www.customfabricate.com)

