

# FST—Filament Strapping Tape

## Specification Sheet

### Description

FST is an economical fiberglass reinforced tape designed for the majority of packaging, palletizing and unitizing applications. The one mil polypropylene film combined with an aggressive “solventless” pressure-sensitive adhesive provides excellent adhesion to corrugated cartons and outstanding holding power.

### Nominal Values

Backing	1.0 MIL (25 u) Biaxially
Orientated	Polypropylene Film
Adhesive	Synthetic Rubber/Resin
Color	Clear, White
Reinforcement	Fiberglass
Adhesion to Steel (oz/in of width) (At 90° peel angle)	48 (13 N/25 mm)
Quick Stick (oz/in of width)	
To Kraft	8 (2.2N/25mm)
To Steel	30 (8.2 N/25mm)
Tensile Strength (lbs/in of width)	100 (438 N/25mm)
Elongation (% at break)	3
Thickness (mils)	4.0 (0,102mm)
Shear to Kraft Paper (hrs.) (1" X 1" X 1000 grams)	Greater than 96



### **Custom Fabricating & Supplies**

5500 Oakwood Park Drive ~ Franklin, WI 53132

P: 414.421.2600 ~ T/F: 800.556.7188 ~ F: 414.421.2700

[www.customfabricate.com](http://www.customfabricate.com)

