

HTC—High Temperature Crepe Tape



Specification Sheet

Description

A general grade, industrial, pressure sensitive masking tape.

Applications

Our HTC offers an excellent balance of quick stick, panel adhesion and holding properties. Not recommended for outdoor exposure.

Technical Properties

- Backing: Smooth Crepe Paper
- Color: Natural
- Adhesive: Natural Rubber/Resin
- Adhesion to Steel: 33 (9 N/25mm)
(oz/in of width)
- Tensile Strength: 20 (88 N/25mm)
(lbs/in of width)
- Elongation: 10
(% at break) PSTC-31
- Total Thickness: 7.5 (0.295 mm)
(mils) PSTC-33
- Quick Stick to Steel: 11 (3 N/25mm)
(oz/in of width) PSTC-5
- Quick Stick to Kraft: 5 (1.4 N/25mm)
(oz/in of width) PSTC-5
- Operating Temperature Range: 50°F to 325°F
10°C to 163°C

Shelf Life

Good for 6 months if kept in a 68 degree environment.



Custom Fabricating & Supplies

5500 Oakwood Park Drive ~ Franklin, WI 53132

P: 414.421.2600 ~ T/F: 800.556.7188 ~ F: 414.421.2700

www.customfabricate.com

