

# HTGV—HIGH TEMP GREEN VINYL

## Specification Sheet

### Description

A 6mil, soft, polyvinyl chloride tape with a synthetic/natural rubber resin blend adhesive. Superior quality with a long shelf-life, provides an effective vapor and moisture barrier, good abrasion, impact and rupture resistance and resistant to aging, sun, water, fungus, bacteria, oil, acids, alkalies and corrosive chemicals.

### Applications

Used for color coding; lane marking and safety coding to meet OSHA requirements. Decorating, striping on vehicles, boats, sporting equipment, etc. Masking of printed circuit boards; harness and pipe wrapping. Duct and joint sealing.

### Technical Properties:

Backing:	Matt Surface, Soft PVC (Polyvinyl Chloride)
Adhesive:	Synthetic/Natural Rubber Resin Blend
Total Thickness:	6.0 mils (0.15 mm)
Adhesion:	17.6 oz./inch
Tensile Strength:	14.3 lbs./inch
Elongation:	150%
Temperature Resistance:	-20°F to +220°F

### Storage

Tape should be stored in a cool, dry area at temperatures of 60 °F to 80 °F and 40% - 50% relative humidity.



### **Custom Fabricating & Supplies**

5500 Oakwood Park Drive ~ Franklin, WI 53132

P: 414.421.2600 ~ T/F: 800.556.7188 ~ F: 414.421.2700

[www.customfabricate.com](http://www.customfabricate.com)

