

HTGV—HIGH TEMP GREEN VINYL

Specification Sheet

Description

A 6mil, soft, polyvinyl chloride tape with a synthetic/natural rubber resin blend adhesive. Superior quality with a long shelf-life, provides an effective vapor and moisture barrier, good abrasion, impact and rupture resistance and resistant to aging, sun, water, fungus, bacteria, oil, acids, alkalies and corrosive chemicals.

Applications

Used for color coding; lane marking and safety coding to meet OSHA requirements. Decorating, striping on vehicles, boats, sporting equipment, etc. Masking of printed circuit boards; harness and pipe wrapping. Duct and joint sealing.

Technical Properties:

Backing:	Matt Surface, Soft PVC (Polyvinyl Chloride)
Adhesive:	Synthetic/Natural Rubber Resin Blend
Total Thickness:	6.0 mils (0.15 mm)
Adhesion:	17.6 oz./inch
Tensile Strength:	14.3 lbs./inch
Elongation:	150%
Temperature Resistance:	-20°F to +140°F

Storage

Tape should be stored in a cool, dry area at temperatures of 60 °F to 80 °F and 40% - 50% relative humidity.



Custom Fabricating & Supplies

5500 Oakwood Park Drive ~ Franklin, WI 53132

P: 414.421.2600 ~ T/F: 800.556.7188 ~ F: 414.421.2700

www.customfabricate.com

