

LFT— Lead Foil Tape

Specification Sheet



Features:

Highly conformable to both irregular and curved surfaces. Aggressive Rubber Pressure Sensitive adhesive is designed To offer excellent quick stick and ultimate adhesion. Liner allows tape to be cut into shapes.

Applications:

Masking: Electroplating, X-ray Plates, Chemical Milling. Sealing: Radioactive Canisters. Shielding: Radiation Barrier.

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness w/o liner	0.0006 inch +/- 10%	ASTM-D-3652
Peel Strength	> 60 ox per inch width	ASTM-D-1000
Breaking Strength	18 lbs./inch of width	ASTM-D-1000
Elongation at Break	15%	ASTM-D-1000
Color	Natural	
Shelf Life	1 year when stored under conditions of 70° F (21° C) and 50% R.H.	

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.



Custom Fabricating & Supplies

5500 Oakwood Park Drive ~ Franklin, WI 53132

P: 414.421.2600 ~ Toll: 800.556.7188 ~ F: 414.421.2700

www.customfabricate.com

