

## PET Metalized Film Tape Technical Data Sheet

### Features:

#MT-60SV is manufactured from 0.9 mil metalized polyester film with brilliant vibrant mirror-like finish, and is coated with an aggressive long lasting acrylic adhesive.

- Excellent chemical and thermal stabilities
- Suitable for reflective shielding industry
- For graphic, artistic and decorative industries
- For trim packaging



### Technical Data :

Item	Test Method	Normal	Minimum
Adhesive		Acrylic	
Carrier		PET Metalized Film	
Carrier Thickness (mil/mm)	ASTM D 1000	0.92 / 0.023	
Total Thickness (mil/mm)	ASTM D 1000	2.16 / 0.055	2.08 / 0.053
Color		Silver	
Adhesion to Steel (N/25mm)/(g/25mm)/(oz/in)	ASTM D 1000	10.7 / 1100 / 38.8	9.8 / 1000 / 35.3
Tensile Strength (N/25mm)/(kg/25mm)/(lb/in)	ASTM D 1000	108 / 11 / 24	98 / 10 / 22
Elongation (%)	ASTM D 1000	100	80
Range of Temperature (°C/F)		-30 ~ 150 / -22 ~ 300	

### Size :

Tape Length (m)	66
Tape Width (mm)	975 available

The information on this data sheet is based on laboratory test data we believe to be accurate, relevant and reliable. Please look upon these values as guides rather than absolutes. Since actual service conditions for a given application may vary substantially from standard laboratory conditions, specific recommendations or warranties relative to a specific end use cannot be made. The buyer is urged to conduct its own investigations and qualification tests to determine suitability for its intended application. CFS shall not be liable for any damages arising out of the use of any of its guide specifications.

Custom Fabricating & Supplies

5500 Oakwood Park Drive | Franklin | WI | 53132 | 414.421.2600 | 800.556.7188 | F: 414.421.2700

[www.customfabricate.com](http://www.customfabricate.com)